PATENT APPLICATION

Storage-Related Accounting System and Method of the Same

Inventors: **Yoshihito Nakagawa**
Citizenship: Japan

Shizuo Yokohata
Citizenship: Japan

Assignee: **Hitachi, Ltd.**
6, Kanda Surugadai 4-chome
Chiyoda-ku, Tokyo, Japan
Incorporation: Japan

Entity: Large

TOWNSEND and TOWNSEND and CREW LLP
Two Embarcadero Center, 8th Floor
San Francisco, California 94111-3834
(415) 576-0200

STORAGE-RELATED ACCOUNTING SYSTEM AND

METHOD OF THE SAME

BACKGROUND OF THE INVENTION

The present invention relates to an accounting system in which accounting can be made on the basis of number of times of access and a data

5 transfer quantity with respect to a storage control device, and relates to an accounting method.

As an accounting method to be used in the case of provision of a storage, there is a fixed accounting method in which a fixed accounting amount is

10 determined for each user in accordance with storage capacity assigned to the user.

As this fixed accounting method, there is provided a method in which fixed accounting with respect to assigned storage capacity is made so that

15 the same account rate is charged to each user assigned to have an equal capacity storage, even though number of times of access or data transfer quantities among the users are different.

SUMMARY OF THE INVENTION

20 An object of the present invention is to provide an accounting system and an accounting method in which an access number-of-time upper limit value and a data transfer-quantity upper limit value for every connected channel port, every connected server, every

connected World Wide Name (WWN), or every storage

device are set so that the number of times of access

and the data transfer quantity can be limited to be not

larger than the respective upper limit values, or so

5 that accounting of number of times of access and a data

transfer quantity larger than the respective upper

limit values can be made.

That is, the storage-related accounting

method according to the present invention has an aspect

10 that not only can fixed accounting with respect to

assigned storage capacity be made, but also accounting

in accordance with number of times of access and a data

transfer quantity of every connected server, number of

times of access and a data transfer quantity of every

15 connected World Wide Name (WWN), number of times of

access and a data transfer quantity of every connected

channel port, number of times of access and a data

transfer quantity of every connected storage device, or

number of times of access and a data transfer quantity

20 of every connected in-storage-device area can be made.

According to the present invention, meter

accounting can be realized by having accounting data

required for calculation of an account amount for every

server, every World Wide Name (WWN), every channel

25 port, every storage device, and every storage area in

every storage device; by making a storage control

device provided with means of measuring the number of

times of access and data transfer quantities; by

recording the measured data as accounting data in the storage control device; and by making accounting in accordance with the recorded accounting data.

Further, meter accounting can be realized by setting an access number-of-time upper limit value and a data transfer-quantity upper limit value for every server, every World Wide Name (WWN), every channel port, every storage device, and every storage area in every storage device; by making a storage control device provided with means of limiting the number of times of access and data transfer quantities to be not larger than the upper limit values; and by making accounting in accordance with the number of times of access and data transfer quantities larger than the upper limit values.

Further, accounting service can be performed by making the storage control device have means of informing the accounting server or the service processor connected to the storage control device of the accounting data stored in the storage control device.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram of the configuration of an accounting system according to an embodiment of the present invention;

Fig. 2 is a table for managing number of times of access and a data transfer quantity of every

host computer in the embodiment;

Fig. 3 is a table for managing number of times of access and a data transfer quantity of every World Wide Name in the embodiment;

5   Fig. 4 is a table for managing number of times of access and a data transfer quantity of every channel port in the embodiment;

Fig. 5 is a table for managing number of times of access and a data transfer quantity of every

10   storage device in the embodiment;

Fig. 6 is a table for managing number of times of access and a data transfer quantity of each storage area in each storage device in the embodiment;

Fig. 7 is a diagram of the configuration of

15   an I/O process control portion;

Fig. 8 is a flow chart of process distribution in response to a request issued to the I/O process control portion;

Fig. 9 is a flow chart of a host-command

20   responding process of the I/O process control portion in response to a request issued by the host computers;

Fig. 10 is a flow chart of a special command responding process of the I/O process control portion in response to a request issued by an accounting

25   server;

Fig. 11 is a flow chart of a service processor responding process of the I/O process control portion in response to a request issued by a service

processor;

Fig. 12 is a table of an upper limit value setting parameter in upper limit value setting requested from the accounting server and the service

5 processor;

Fig. 13 is a flow chart in which the server accounting requests setting of upper limit values of a WWN as an accounting subject control unit;

Fig. 14 is a flow chart in which the

10 accounting server fetches accounting data from the storage control device; and

Fig. 15 is a flow chart showing the whole of the accounting system.

DETAILED DESCRIPTION OF THE EMBODIMENTS

15 The present invention will be described below with reference to the drawings.

Fig. 1 is a diagram showing an embodiment of a storage-related accounting system according to the present invention. In the storage-related accounting

20 system of Fig. 1, a WWN 105 of a host computer 101, a WWN 106 of the same host computer 101, a WWN 107 of a host computer 102, a WWN 108 of a host computer 103, a WWN 109 of a host computer 104, and an accounting server 801 are connected to channel ports 501 to 504 of

25 a storage control device 401 through a channel path 201, through a channel path 202, a HUB 301 and a channel path 204, through a channel path 203, the HUB

301 and the channel path 204, through a channel path

205, a SWITCH 302 and a channel path 207, through a

channel path 206, the SWITCH 302 and the channel path

207, and through a channel path 208, respectively.

5 Incidentally, the storage control device 401 and the

host computers 101 to 104 are connected through serial

channels, for example, of optical fibers so as to

constitute a LAN.

The storage control device 401 is constituted

10 by the channel ports 501 to 504, I/O process control

portions 601 to 604 and a shared memory 605. The I/O

process control portions 601 to 604 control the I/O

process which is requested to areas 704, 705, 706 ...

of a plurality of storage devices 701, 702, 703 ...

15 from the host computers 101 to 104. The I/O process

control portions 601 to 604 can make access to the

shared memory 605.

The I/O process control portions 601 to 604

perform data I/O operation to/from the plurality of

20 storage devices 701 to 703.

A service processor 901 is connected to each

of the I/O process control portions 601 to 604.

Figs. 2 to 6 are accounting information

tables provided in the shared memory 605.

25 Each of the accounting information tables

holds, as accounting data, the number of times of

access and the data transfer quantity for every control

unit which will be the accounting subject.

Specifically, the control unit may include the connection-end host computer, the World Wide Name (WWN), the storage-end storage device, the storage area in the storage device, and so on.

5   When the number of times of access and a data transfer quantity are accounted for every host computer, the host computer accounting information table 606 shown in Fig. 2 is updated by the I/O process control portions 601 to 604 so that the accounting data

10   is generated for every host computer. An access number-of-time integrated value 607 is a value obtained by integrating the number of times of access from the host computer 101. A data transfer-quantity integrated value 608 is a value obtained by integrating the data

15   transfer quantity given from the host computer 101. An access number-of-time upper limit value 609 is number of times of access given from the host computer 101 and allowed to be processed in one second. A data transfer-quantity upper limit value 610 is a data

20   transfer quantity given from the host computer 101 and allowed to be processed in one second. An access number-of-time upper limit value 611 for supervising the upper limit value is an integrated value obtained by integrating the number of times of access given from

25   the host computer 101 in one second. A data transfer-quantity upper limit value 612 for supervising the upper limit value is an integrated value obtained by integrating the data transfer quantity given from the

host computer 101 in one second. An upper limit value supervising start time 613 is a time when the number of times of access or the data transfer quantity given from the host computer 101 in one second starts to be

5 measured. The host computer 102 also has the same table as the host computer 101, and each of the host computers 103 and 104 has the same table, too.

When the number of times of access and the data transfer quantity are accounted for every WWN, a

10 WWN accounting information table 614 shown in Fig. 3 is updated by the I/O process control portions 601 to 604 so that the accounting data for every WWN is generated. An access number-of-time integrated value 615 is a value obtained by integrating the number of times of

15 access given from the WWN 105. A data transfer- quantity integrated value 616 is a value obtained by integrating the data transfer quantity given from the WWN 105. An access number-of-time upper limit value 617 is the number of times of access given from the WWN

20 105 and allowed to be processed in one second. A data transfer-quantity upper limit value 618 is a data transfer quantity given from the WWN 105 and allowed to be processed in one second. An access number-of-time upper limit value 619 for supervising the upper limit

25 value is an integrated value obtained by integrating the number of times of access given from the WWN 105 in one second. A data transfer-quantity upper limit value 620 for supervising the upper limit value is an

integrated value obtained by integrating the data

transfer quantity given from the WWN 105 in one second.

An upper limit value supervising start time 621 is a

time when the number of times of access or data

5   transfer quantity given from the WWN 105 in one second

starts to be measured.   The WWN 106 also has the same

table as the WWN 105, and each of the WWNs 107 to 109

has the same table, too.

When the number of times of access and the

10 data transfer quantity are accounted for every channel

port, a channel port accounting information table 622

shown in Fig. 4 is updated by the I/O process control

portions 601 to 604 so that the accounting data for

every channel port is generated.

15   An access number-of-time integrated value 623

is a value obtained by integrating the number of times

of access given through the channel port 501.   A data

transfer-quantity integrated value 624 is a value

obtained by integrating the data transfer quantity

20 given through the channel port 501.   An access number-

of-time upper limit value 625 is the number of times of

access given through the channel port 501 and allowed

to be processed in one second.   A data transfer-

quantity upper limit value 626 is a data transfer

25 quantity given through the channel port 501 and allowed

to be processed in one second.   An access number-of-

time upper limit value 627 for supervising the upper

limit value is an integrated value obtained by

integrating the number of times of access given through
the channel port 501 in one second. A data transfer-
quantity upper limit value 628 for supervising the
upper limit value is an integrated value obtained by

5   integrating the data transfer quantity given through
the channel port 501 in one second. An upper limit
value supervising start time 629 is a time when the
number of times of access or data transfer quantity
given through the channel port 501 in one second starts

10   to be measured. The channel port 502 also has the same
table as the channel port 501, and each of the channel
ports 503 and 504 has the same table, too.

     When the number of times of access and the
data transfer quantity are accounted for every storage

15   device, a storage device accounting information table
630 shown in Fig. 5 is updated by the I/O process
control portions 601 to 604 so that accounting data for
every storage device is generated.

     An access number-of-time integrated value 631

20   is a value obtained by integrating the number of times
of access to the storage device 701. A data transfer-
quantity integrated value 632 is a value obtained by
integrating the data transfer quantity given to the
storage device 701. An access number-of-time upper

25   limit value 633 is the number of times of access given
to the storage device 701 and allowed to be processed
in one second. A data transfer-quantity upper limit
value 634 is a data transfer quantity given to the

storage device 701 and allowed to be processed in one second. An access number-of-time upper limit value 635 for supervising the upper limit value is an integrated value obtained by integrating the number of times of

5   access given to the storage device 701 in one second. A data transfer-quantity upper limit value 636 for supervising the upper limit value is an integrated value obtained by integrating the data transfer quantity given to the storage device 701 in one second.

10   An upper limit value supervising start time 637 is a time when the number of times of access or data transfer quantity given to the storage device 701 in one second starts to be measured. The storage device 702 also has the same table as the storage device 701,

15   and the storage device 703 et seq. has the same table, too.

       When the number of times of access and the data transfer quantity are accounted for every area in every storage device, an in-storage-device area

20   accounting information table 638 shown in Fig. 6 is updated by the I/O process control portions 601 to 604 so that accounting data is generated for every in-storage-device area.

       An access number-of-time integrated value 639

25   is a value obtained by integrating the number of times of access to the in-storage-device area 704. A data transfer-quantity integrated value 640 is a value obtained by integrating the data transfer quantity

given to the in-storage-device area 704. An access

number-of-time upper limit value 641 is the number of

times of access given to the in-storage-device area 704

and allowed to be processed in one second. A data

5   transfer-quantity upper limit value 642 is a data

transfer quantity given to the in-storage-device area

704 and allowed to be processed in one second. An

access number-of-time upper limit value 643 for

supervising the upper limit value is an integrated

10 value obtained by integrating the number of times of

access given to the in-storage-device area 704 in one

second. A data transfer-quantity upper limit value 644

for supervising the upper limit value is an integrated

value obtained by integrating the data transfer

15 quantity given to the in-storage-device area 704 in one

second. An upper limit value supervising start time

645 is a time when the number of times of access or the

data transfer quantity given to the in-storage-device

area 704 in one second starts to be measured. The in-

20 storage-device area 706 also has the same table as the

in-storage-device area 704

Fig. 7 is a diagram showing a process

configuration of each of the I/O process control

portions 601 to 604 by a computer program. In process

25 distribution (Step 1001), a host-command responding

process (Step 1002), a special command responding

process (Step 1003) or a service processor responding

process (Step 1004) in response to the request contents

to the I/O process control portions 601 to 604 are executed.

The host-command responding process (Step 1002) is constituted by a command process (Step 1005), 5 an accounting data generating process (Step 1006), and an upper limit value supervising process (Step 1007). In the command process (Step 1005), a process from the host computers 101 to 104 is executed. In the accounting data generating process (Step 1006), 10 accounting data is generated in accordance with access or data transfer made in the command process (Step 1005). In the upper limit value supervising process (Step 1007), access and data transfer are supervised and limited so as to be not larger than a predetermined 15 access number-of-time upper limit value and a predetermined data transfer-quantity upper limit value, respectively.

The special command responding process (Step 1003) is constituted by an upper limit value setting 20 process (Step 1008) and an accounting data transmitting process (Step 1009). In the upper limit value setting process (Step 1008), in response to the request from the accounting server 801 for setting of the access number-of-time upper limit values and the data 25 transfer-quantity upper limit values, the access number-of-time upper limit values and the data transfer-quantity upper limit values are set respectively for the host computer accounting

information table 606, the WWN accounting information table 614, the channel port accounting information table 622, the storage device accounting information table 630 and the in-storage-device area accounting

5 information table 638, which are all stored in the shared memory 605. On the other hand, in the accounting data transmitting process (Step 1009), in response to the request from the accounting server 801 for sending accounting data, the access number-of-time

10 integrated values and the data transfer-quantity integrated values respectively for the accounting information tables 606, 614, 622, 630 and 638, which are all stored in the shared memory 605 are sent to the accounting server 801.

15   Fig. 8 is a chart showing a flow of the process distribution (Step 1001) in the I/O process control portion 604. In the flow of Fig. 8, in the process distribution (Step 1001), a request is accepted (Step 1101), and then a host-command responding process

20 (Step 1002) shown in Fig. 7 is executed when the accepted request is a host command from one of the host computers 101 to 104 (Step 1102), or a special command responding process (Step 1003) is executed when the accepted request is a special command (Step 1103) from

25 the accounting server 801, or a service processor responding process (Step 1004) shown in Fig. 7 is executed when the accepted request is a request from the service processor (Step 1004).

Fig. 9 is a flow chart of the host responding process (Step 1002) executed in the process distribution (Step 1001) when there is a request from any one of the host computers 101 to 104.

5   When the request from the host computer 101, 102, 103 or 104 is neither a READ process nor a WRITE process (Step 1201), a command process in response to the request is executed (Step 1005) and completed.

When the request from the host computer 101, 102, 103 or 104 is a READ process or a WRITE process, and neither the respective access number-of-time upper limit values nor the data transfer-quantity upper limit values are set in every host computer, in every WWN, in every channel port, in every storage device, and in every in-storage-device area (Step 1202), a command process in response to the request (Step 1005) is executed. Then, 1 (one) is added to the access number-of-time integrated value in corresponding one of the accounting information tables 606, 614, 622, 630 and 638 of the host computer, the WWN, the channel port, the storage device, and the in-storage-device area which has responded to the request respectively, all the table being stored in the shared memory 605, while a requested data transfer quantity is added to the data transfer-quantity integrated value in the corresponding one of the accounting information tables 606, 614, 622, 630 and 638. Thus, the process is completed (Step 1006).

In the case where the access number-of-time upper limit value 618 in the WWN accounting information table 614 stored in the shared memory 605 is set to any value other than zero, and the access number-of-time

5 upper limit value to WWN 105 is set, if a READ or WRITE process is executed through the WWN 105 of the host computer 101 (Step 1201), the upper limit value supervising start time in the WWN accounting information table 614 is read and the elapsed time from

10 the start time to the present time is calculated (Step 1203), because the access number-of-time upper limit value is set in the WWN 105. If the elapsed time is longer than one second (Step 1204), the access number-of-time upper limit value 619 for supervising the upper

15 limit value in the WWN accounting information table 614 is cleared (Step 1205). Then, the present time is set as the upper limit value supervising start time 621 (Step 1206), the command process (Step 1005) in response to the request is executed, and 1 (one) is

20 added to the access number-of-time upper limit value 619 for supervising the upper limit value.

If the measured time is shorter than one second and the access number-of-time upper limit value 619 for supervising the upper limit value is smaller

25 than the access number-of-time upper limit value 618, the command in response to the request is executed (Step 1005) and 1 (one) is added to the access number-of-time upper limit value 619 for supervising the upper

limit value.

If the measured time is shorter than one second (Step 1204) and the access number-of-time upper limit value 619 for supervising the upper limit value is not smaller than the access number-of-time upper limit value 618, the command process (Step 1005) is suppressed until one second or more elapsed. Accordingly, the request (the number-of-times of access per second) from the WWN 105 cannot exceed the access number-of-time upper limit value 618 (Step 1207).

Fig. 10 is a flow chart of the special command responding process (Step 1003) for executing a process in response to the request from the accounting server 801. Fig. 11 is a flow chart of the service processor responding process (Step 1004) for executing a process in response to the request from the service processor 901.

In the flow chart of Fig. 10 or 11, if the request from the accounting server 801 or service processor 901 is not for setting of the upper limit value (Step 1301 or 1401), the access number-of-time integrated values and the data transfer-quantity integrated values in the accounting information tables 606, 614, 622, 630 and 638 respectively stored in the shared memory 605 are sent to the accounting server 801 or service processor 901.

Detailed description about the Step 1008 in Fig. 10 or 11 will be made later.

Fig. 12 is a view showing an upper limit

value setting parameter 1501 when there is an upper

limit value setting request from the accounting server

801 or service processor 901. The upper limit value

5   setting parameter 1501 is constituted by: a unit

information 1502 for showing a unit such as a host

computer, a WWN, a channel port, or the like; a unit

detailed information 1503 for setting the details of

the unit; a period information 1504 for setting one

10 month, one hour, or one week; number of times of access

1505 which are allowed to be made in the period; and a

data transfer quantity 1506 which is allowed to be made

in the period.

The flow in Fig. 10 or 11 will be described

15 in the case where there is an access number-of-time

upper limit value setting request to the WWN 105 from

the accounting server 801 or service processor 901.

When there is a request to set the upper

limit value from the accounting server 801 or service

20 processor 901 (Step 1301 or 1401), the WWN 105 is

identified on the basis of the unit information 1502

and the unit detailed information 1503 in the upper

limit value setting parameter 1501 (Step 1302 or 1402).

An access number-of-time upper limit value in one

25 second is obtained on the basis of the period

information 1504 and the number of times of access 1505

in the upper limit value setting parameter 1501 (Step

1303 or 1403). Then, the obtained access number-of-

time upper limit value is set as the access number-of-time upper limit value 617 in the WWN accounting information table 614 stored in the shared memory 605.

Next, (1) under the condition that no access
5   number-of-time upper limit value is set for WWN 105, (2) under the condition that an access number-of-time upper limit value is set for the WWN 105 but there is no limit in the access to the WWN 105, and (3) under the condition that an access number-of-time upper limit
10   value is set for the WWN 105 and there is a limit in the access to the WWN 105, description will be made respectively about the examples of the method how the accounting server 801 calculates the rate on the basis of the accounting data.

15   (1) Under the condition that no access number-of-time upper limit value is set for the WWN 105, the rate for the access number-of-time integrated value 615 which is the accounting data sent from the storage control device 401 will be calculated in a
20   manner as follows.

rate = (access number-of-time integrated value [number of times] x one access rate [¥/number of times]) + (storage capacity [MByte] x capacity unit price [¥/MByte])

25   Thus, this rate is calculated on the basis of meter accounting of the number of times of the access.

Further, if one access rate is set to 0 [¥/number of times], the rate will be a fixed amount because only the storage capacity is accounted.

(2) Under the condition that there is an
5 access number-of-time upper limit value for the WWN 105 but there is no limit in the access to the WWN 105, the rate for the access number-of-time integrated value 615 which is the accounting data sent from the storage control device 401 will be calculated in a manner as
10 follows.

In the case where the access number-of-time upper limit value is equal to or than the access number-of-time integrated value:

rate = (access number-of-time upper limit value [number
15 of times] x one access rate [¥/number of times]) + (storage capacity [MByte] x capacity unit price [¥/MByte])

In the case where the access number-of-time upper limit value is smaller than the access number-of-time
20 integrated value:

rate = (access number-of-time upper limit value [number of times] x one access rate [¥/number of times]) + ((access number-of-time integrated value [number of times] - access number-of-time upper limit value
25 [number of times]) x one access rate [¥/number of

times] when the integrated value is larger than the
upper limit value) + (storage capacity [MByte] x
capacity unit price [¥/MByte])

This rate because a meters accounting in accordance
5   with the number of times of access based on one access
rate indicating over the upper limit value which is
equal to or larger than one access rate.

        (3) Under the condition that an access
number-of-time upper limit value is set for the WWN 105
10   and there is a limit in the access to the WWN 105,
because the number of times of access is limited to be
not larger than the upper limit value, the rate will be
calculated in a manner as follows.

rate = (access number-of-time upper limit value [numebr
15   of times] x one access rate [¥/number of times]) +
(storage capacity [MByte] x capacity unit price
[¥/MByte])

Thus, this rate will be a fixed amount.
        In such a manner, according to the
20   embodiment, the number of times of access and the data
transfer quantity for every host computer, every World
Wide Name (WWN), every channel port, every storage
device and every in-storage-device area are generated
as accounting data in the storage control device. An
25   accounting server can realize a meter accounting rate

system in accordance with the accounting data generated
in the storage control device.

Next, a specific example for setting the
access number-of-time upper limit value for the WWN 105
5   from the accounting server 801 will be described with
reference to the flow chart of Fig. 13 and Fig. 12.
First, a user chooses setting or not-setting of an
upper limit value request (Step 1601). If there is an
upper limit value request (Step 1602), the user enters
10   information of the unit as the subject for setting the
upper limit value. Here, assume that the user chooses
"WWN" as the unit information (Step 1603). Next, "WWN"
is set as unit information 1502 of the upper limit
value setting parameter 1501 (Step 1604). The user
15   enters the number of the WWN "105" in unit detailed
information for setting the upper limit value (Step
1605). Then, the number of the WWN "105" is set as the
unit detailed information 1503 (Step 1606). Next, the
user enters one day in period information (Step 1607)
20   and "one day" is set as the period information 1504
(Step 1608). Next, the user enters "86400" in the
access number-of-time upper limit value (Step 1609).
Here, "86400" is set as the number of access times 1505
(Step 1610). The user then sends the thus set upper
25   limit value setting parameter 1501 to the storage
control device 401 (Step 1611). In such a manner, as a
control unit, that is, as an accounting subject, the
upper limit value for accounting is determined for a

specified WWN. Although the above example has
described about the process of setting an upper limit
value requested from the accounting server 801, the
same process will be executed if setting of an upper

5   limit value is requested from the service processor
901.

Further, a specific example in which the
accounting server 801 fetches the accounting data every
predetermined period from the shared memory 605 of the

10   storage control device 401 will be described in
accordance with the flow chart of Fig. 14. First, a
judgement is made as to whether a predetermined time
after the fetching of the last accounting data elapsed
or not (Step 1701). If the predetermined time elapsed,

15   a request of sending accounting data is issued to the
storage control device 401 (Step 1702). Waiting is
made until the accounting data is received (Step 1703).
The accounting server 801 records the received
accounting data in a database of the accounting server

20   801 (Step 1704). Although the above example has
described about the case where the accounting server
801 has requested the accounting data, the same process
will be executed if the service processor 901 requests
the accounting data from the storage control device

25   401.

Fig. 15 is a flow chart from the step of the
above-mentioned upper limit value setting request
issued from the accounting server 801 to the storage

control device 401 to the step of fetching the

accounting data stored in the shared memory 605 of the

storage control device 401 into the accounting server

801. The accounting server 801 makes an upper limit

5 value setting request to the storage control device 401

(Step 1801). After that, waiting is made for lapse of

a predetermined time (Step 1802).

On the other hand, if the storage control

device 401 receives the upper limit value setting

10 request from the accounting server 801, the upper limit

value setting is performed in associated one of the I/O

process control portions 601 to 604 (Step 1901). Next,

the associated one of the I/O process control portion

601 to 604 fetches accounting data from the associated

15 one of the host computers 101 to 104 into the storage

control device 401 (Step 1902). The I/O process is

determined whether it is executed or restrained for the

upper limit value set in Step 1901 (Step 1903), and

accounting data is generated (Step 1904).

20 After a predetermined time elapsed, the

accounting server 801 issues an accounting data sending

request to the storage control device 401 (Step 1803).

In response to the request, the storage control device

401 sends the accounting data to the accounting server

25 801 (Step 1905). After then, the accounting server 801

records the received accounting data in the database

(Step 1804). Incidentally, the accounting data

mentioned here means the contents of the accounting

information tables shown in Fig. 2 through 6. Further,
as described in Figs. 13 and 14, the same process shown
in Fig. 15 will be executed if an upper limit value
setting request is issued from the service processor
5   901 to the storage control device 401.

According to the present invention, it is
therefore possible to make accounting in accordance
with the number of times of access and the data
transfer quantity of each user of a plurality of users
10   to whom equal storage capacity is assigned, even though
the number of times of access or data transfer quantity
made by each user may be different.